



# 4700 SLIDING DOOR

TBB

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

**$U_w$  from 1.1 (W/m<sup>2</sup>K)**

Please consult typology, dimensions and glazing.

## ACCOUSTIC INSULATION

Maximum glazing: **34 mm**

Maximum acoustic insulation: **Rw = 40 dB**

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

**Class 3**

Water tightness (EN 12208):

**Class 7A**

Wind resistance (EN 12210):

**Class C5**

\*Reference test 1.80 x 2.20 m 2 sashes

SECTIONS	Frame 120 mm and 115 mm Three-rail 185 mm Sash 50 mm
PROFILE THICKNESS	Balcony 1.5 mm
MAXIMUM DIMENSIONS	Width (L) = 2.500 mm Height (H) = 3.000 mm
MAXIMUM WEIGHT/SASH	280 Kg

Please consult maximum dimensions according to types.

EXTRUSION ALLOY
6063 T-5
POLYAMIDE STRIP LENGTH
Polyamide 6.6 reinforced with 25% fiberglass : 20 y 25 mm
OPENING POSIBILITIES
Sliding door 2, 3, 4 and 6 sashes Optionally mono-rail (Sash+fix) Optionally Two-rail, three-rail Galandage

## FINISHES

Colour powder coating  
(RAL, mottled, rough...)

According to Qualicoat > 60 microns

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras

Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

